

SURFACE FINISHING EQUIPMENT GROUP

www.sfeg.co.uk

SALES – SERVICE - HIRE - TRAINING – INSTALLATION

NORTHEAST BRANCH

Hogg Blasting & Finishing Equipment Ltd
Washington. UK. NE37 1PR

Tel. 0191 415 3030
info@hoggblasting.com

NORTHWEST BRANCH

Abraclean Ltd
and
Jedtec Finishing Equipment
Manchester, UK. M11 2QA

Tel: 0161 480 8087
sales@sfeg.co.uk

- Shot Blasting Equipment
- Paint Spraying Equipment
- Powder Coating Equipment
- Fixed Extraction Booths
- Mobile Dust Extraction
- Personal Protection Equipment
- Shot Blasting Abrasives
- Spares and Consumables
- Plural Component Systems

Complete Finishing Systems
Tipton. UK. DY4 7TR

Tel. 01902 601 312
info@sfeg.co.uk

- Complete Finishing Plants
- Spray Booths
- Design engineers and CAD
- Industrial Ovens
- Conveyors
- Pre-treatment systems
- Powder Coating Booths and equipment

Munkebo Abrasive Recovery DS-36-1



Munkebo 3000 Abrasive Recovery Unit

The Munkebo abrasive recovery unit is designed for the retrieval and transport of abrasive media. The machine is electrically powered and designed to substantially reduce abrasive retrieval and site cleaning costs. Re-usable abrasive can be recycled or expendable abrasive emptied into a skip for disposal.

The units are driven by a high powered electric induction motor coupled to a heavy duty vacuum pump. The cyclone filter section is fitted with safety relief valve and automatically sequenced reverse jet filter system.

The Munkebo can recover spent abrasive up to 75 metres (using the MB3000), depending on abrasive size and type.

The recovered media is collected in a storage silo where it can either be re-used or emptied into a waste skip, as required.

The Munkebo is available for sale or hire in 2 sizes and is normally used in conjunction with a media Storage Silo.

SPECIFICATION

MODEL	MB-2000	MB-3000
Dimensions (metres)	2.3 x 1.5 x 2.4	3.0 x 1.5 x 2.4
Dry Weight (kg)	2100kg	2850kg
Power Required	45Kw - 415V 3 phase	75Kw - 415V 3 phase
Generator Required	125KVA	200 KVA with DB Board
Generator Breaker Required	125 amp Type D Breaker	200 amp Type D Breaker
Recovery Rates	3-10 T/hr	3-15 T/hr
Max Recovery Distance	40m	70m

Note : These products provide optimum and safe performance only when used in accordance with manufacturer's instructions, with suitably trained operators, and when provided with adequate recommended power requirements.