

SURFACE FINISHING EQUIPMENT GROUP

www.sfeg.co.uk

SALES – SERVICE - HIRE - TRAINING – INSTALLATION

NORTHEAST BRANCH

Hogg Blasting & Finishing Equipment Ltd
Washington. UK. NE37 1PR

Tel. 0191 415 3030
info@hoggblasting.com

NORTHWEST BRANCH

Abraclean Ltd
and
Jedtec Finishing Equipment
Manchester, UK. M11 2QA

Tel: 0161 480 8087
sales@sfeg.co.uk

- Shot Blasting Equipment
- Paint Spraying Equipment
- Powder Coating Equipment
- Fixed Extraction Booths
- Mobile Dust Extraction
- Personal Protection Equipment
- Shot Blasting Abrasives
- Spares and Consumables
- Plural Component Systems

Complete Finishing Systems
Tipton. UK. DY4 7TR

Tel. 01902 601 312
info@sfeg.co.uk

- Complete Finishing Plants
- Spray Booths
- Design engineers and CAD
- Industrial Ovens
- Conveyors
- Pre-treatment systems
- Powder Coating Booths and equipment

Ultramax and Mark V Sprayers DS-X



Graco 695 Procontractor (left)

and



Graco Standard Series (right)

The Ideal choice for the professional spray painter. Ideally suited to interior or exterior painting jobs - renovation, new construction, and commercial contractors.

- Manufactured by Graco - a world-wide leader in spray painting equipment.
- Fully CE marked 110 volt European model backed by UK warranty.
- Supplied ready to go with gun, line, tip, toolkit, and bottle of TSL oil.

Typical uses :

- Enamels, emulsions, urethanes, acrylic, latex and epoxies.
- Mark V model also suitable for fire retardant / intumescent coatings.
- Max Pressure - 3300psi.
- Auto Clean two system cleans gun, hose, filters and unit independently.
- Watch Dog protection system preventing pump runaway and damage.
- Features long life seals, and hardened steel cylinder.
- Easy clean pump filter reduces tip clogs and ensures a quality finish.

Procontractor Models also feature :

- Hose reel, LED Display, Vortex wet end to extend piston life, quick release wet end.

MODELS AND SPECIFICATIONS

Model	Code	Description	Max Tip Size One gun (Th)	Max Flow (l/min)	Motor (kW)	Weight (kg)
695	17E634	Standard	31	3.6	1.3	43
695	17E637	Procontractor	31	3.6	1.3	50
Mark V	17E659	Standard	39	5.1	2.0	59
Mark V	17E662	Procontractor	39	5.1	2.0	66

Note : These products provide optimum and safe performance only when used in accordance with manufacturer's instructions, with suitably trained operators, and when provided with adequate recommended power requirements.