



## ***RansFlex® Electrostatic Applicator*** **LIGHTWEIGHT AND ERGONOMIC**

Best in class atomization in a compact, lightweight applicator, the new U.S. made RansFlex applicator offers new features and benefits that surpass all other applicators in the industry today. The competition just doesn't stack up.

The RansFlex is an air atomizing electrostatic applicator powered by an onboard generator. Designed with the operator in mind, the RansFlex handle incorporates many grip/handle improvements with better balanced weight to reduce operator fatigue. DeVilbiss atomization technology is coupled with Ransburg power to provide superior atomization and performance backed by a 5-year limited warranty.

Utilizing 20% fewer parts than previous models, the RansFlex is easier to maintain. The patented turbine utilizes a three-phase motor to reduce vibration and provide electrostatic power. RansFlex incorporates quick air hose disconnect technology at the handle to reduce "treeing" and integrates color coded nozzles for easy identification. Indexing air cap and quick voltage on/off knob makes finishing a snap.

***Performance, balance, operator comfort, transfer efficiency and ease of maintenance . . . That's RansFlex meeting the finishing needs of today and tomorrow.***

---

***Superior Air Cap Performance  
 At Lower Inlet Pressure***

***5-Year Limited Warranty***



# RansFlex® Electrostatic Applicator

LIGHTWEIGHT AND ERGONOMIC

Ransburg

## Features and Benefits

- **Ergonomic fit, feel, balance and controls** - Operators experience less stress on joints and muscles which has proven to lower the risks of carpal tunnel and the impact of physical strain, reducing fatigue.
- **Redesigned sleek and smooth exterior** - Makes cleaning and maintenance fast and easy while protecting strategic components.
- **Provides three phases of generator protection** - Includes divorced generator air supply cartridge, sealed nozzle/atomization passages and strategic turbine location.
- **Meets FM/ATEX/CSA** - Complies with all globally recognized standards and promotes quality confidence for specification and purchase.
- **Reverse “cheeks” and formed trigger** - Adds stability to the grip in the palm area while promoting easier resting in the fingers and enhanced comfort for the “V” in the operators hand.



**RansFlex provides a unique combination of DeVilbiss atomization with the cascade power of Ransburg. Users gain higher performance in a smaller, lighter applicator.**

## Specifications – Two Models Available

### RansFlex RX

Weight without hoses	599g (21.3 oz.)
Height	190.5 mm (7.5")
Width Max	41.2 mm (1 5/8")
Length	254,0 mm (10")
Operating Voltage	45 kV
Max Current	140 mA
Min Inlet Pressure	2.8 bar (40 psig) (dynamic at handle inlet)
Paint Conductivity	.1 MΩ to infinity
Fluid Flow Capacity	1,000 ml/min.*
Consumption with Voltage	4385 lpm (15.4 scfm) 2.8 bar (40 psig) (at handle inlet)
Material	Solvent Base

### RansFlex RFX

Weight without hoses	620g (22.0 oz.)
Height	190.5 mm (7.5")
Width Max	41.2 mm (1 5/8")
Length	273 mm (10 3/4")
Operating Voltage	65 kV
Max Current	120 mA
Min Inlet Pressure	2.8 bar (40 psig) (dynamic at handle inlet)
Paint Conductivity	.1 MΩ to infinity
Fluid Flow Capacity	1,000 ml/min.*
Material	Solvent Base

\* depends on material viscosity and tip size selected

## Ransburg

320 Phillips Ave.  
Toledo, Ohio 43612-1493 USA  
Toll Free: 800-909-6886  
Fax: 419-470-2233  
marketing@ransburg.com  
www.ransburg.com

IL-8875, 4/2015

Copyright 2015 Ransburg. All rights reserved. Models and specification subject to change without notice.

DeVILBISS

Ransburg

BGK

BINKS

Finishing Brands