

# TriTech



### TriTech Airless

## TriTech.

T9

**3.97** Itrs/min

**0.031"** Max tip

#### Use to spray

Emulsion, interior and exterior
Majority of high-viscosity water or solvent based coatings with a solid content up to 70%
Intumescents



TriTech

✓ Decorative

✓ Industrial

✓ Intumescent

#### **Product Codes**

110 volt 602-823 240 volt 602-814

#### **Complete with**

TriTech T380 Contractor spray

TriTech Contractor 517 airless tip TriTech Contractor safety guard 1/4" x 15m textile hose assembly QLube x 237ml piston lubricant

#### **Specification**

Flow 3.97 ltr/min Max tip 0.031" MWP 227 bar | 3300 psi Motor 1565 watt PMDC Weight 44.0 kg Power supply 110 / 240 volt

#### **Features**

Designed, engineered and built - all in the USA Aerospace grade materials used throughout

High grade aluminium for the control box, motor cover and heat sink - aluminium dissipates heat, as opposed to plastic which retains it

Steel cut and precision ground gears - running in synthetic grease for positive heat transfer

Frame from chrome plated heavy walled steel tubing, immensely strong and tough

TriTech proprietary carbide blend is used for the ball and seat to give a superior and positive shut off All covered by the unique TriTech warranty