AIRLESS SPRAY TIPS



| Tip size - Thou. Inch | Material | | | | |
|-----------------------|----------------------|--|--|--|--|
| 007 – 009 | Dyes | | | | |
| 009 – 011 | Ink | | | | |
| 011 – 013 | Stains Lacquers Oils | | | | |
| 011 – 015 | Enamels | | | | |
| 013 – 015 | Urethanes | | | | |
| 015 – 019 | Latex | | | | |
| 015 – 019 | Acrylics | | | | |
| 017 – 021 | Emulsions | | | | |
| 023 – 031 | Block fillers | | | | |
| 029 - 035 | Intumescents | | | | |
| 031 – 043 | Epoxies | | | | |

AIRLESS SPRAY TIPS INFORMATION


An airless spray pump pressurises the material being sprayed and forces it through the small orifice of the spray tip under high pressure. This process atomizes the paint in a controlled fan width and flow rate.

Choosing the correct tip will decrease overspray, provide the correct finish at the correct thickness, provide more control, and use less paint.

• When a spray tip wears the orifice gets rounder which makes the fan pattern smaller. When a tip with a 12 inch wide fan pattern wears to a 9 inch fan pattern it uses 30% more paint over a 25% less area.

Getting the most from your spray tip depends on several factors:

- Fan width picked to match the size of the object being sprayed.
- Orifice size suited to the type of paint you are spraying and thickness required.
- Pump Output each pump can only handle a tip up to a certain size.



| ORDER CODES | | | | | | | | |
|--|---------|--------|---|--------------|----------------------|-------------|-----------------------------|--|
| Description | Code | Colour | Typically used with | Max Pressure | Size Range (thou) | Holder Code | Seals / Seat Kit | |
| Reversible Tips - can be turned through 180 degrees to clear blockages | | | | | | | | |
| XHD RAC | XHD-xxx | Grey | NXT Pneumatic Pumps | 7250psi | 7 - 81 | XHD001 | XHD010 | |
| RAC X Fine Finish | FFA-xxx | Green | Electric Pumps Petrol Pumps Merkur / G40 Air-Assisted Pumps | 4050psi | 8 - 14 | 246215 | 246453 Standard | |
| RAC X Standard | PAA-xxx | Blue | | 4050psi | 15 - 25 | 246215 | 248936 Strong | |
| RAC X HD | HDA-xxx | Brown | Electric or Petrol Pumps | 4050psi | 27 - 71 | 246215 | Solvents | |
| Linelazer | LL5-xxx | Yellow | Linelazer | 4050psi | 13 - 55 | 243161 | 243281 | |
| Non Reversible Tips - flat or button type | | | | | | | | |
| Button Tip AA | GG4-xxx | Metal | G15 / G40 Air Assisted | | 7 - 39 | 24D439 | | |
| Button Tip Fine | 163-xxx | Metal | All pumps | 4050psi | 08 - 32 | 220251 | 166969 Thin 162863 Thick | |
| Button Tip | 269-xxx | Metal | All pumps | 5000psi | 11 - 35 | 220251 | 102003 IIIICK | |









