

THE SURFACE FINISHING EQUIPMENT GROUP

SALES – SERVICE - HIRE
TRAINING – INSTALLATION

NORTH EAST BRANCH

**Hogg Blasting
& Finishing Equipment Ltd**
Washington. UK. NE37 1PR

Tel. 0191 415 3030
info@hoggblasting.com

NORTH WEST BRANCH

**Abraclean Ltd and
Jedtec Finishing Equipment**
Stockport. UK. SK5 7PP

Tel: 0161 480 8087
sales@abraclean.co.uk

- Shot Blasting Equipment
- Paint Spraying Equipment
- Powder Coating Equipment
- Fixed Extraction Booths
- Mobile Dust Extraction
- Personal Protection Equipment
- Shot Blasting Abrasives
- Spares and Consumables
- Plural Component Systems

Ercon Finishing Systems
Willenhall. UK. WV13 2JW

Tel. 01902 601 312
sales@erconfinishing.com

- Complete Finishing Plants
- Design engineers and CAD
- Industrial Ovens
- Conveyors
- Pre-treatment systems
- Electroplating Systems



Surface Finishing
Equipment Group

COMMANDER II BLAST HELMET



Honeywell
SPERIAN

The selection and use of the correct Personal Protective Equipment is essential to effectively protect employees from risk or harm by creating a barrier against workplace hazards.

As part of a system our Commander II – popular known as “The Defender” Blast Helmet provides essential protection from impact of abrasive, noise, and respiratory hazards. This helmet is a popular choice with contractors due to its simple rugged design.

SPECIFICATIONS

Respiratory Standards	BS EN 271:1995
Assigned Protection Factor	1000
Air Supply Requirements	> 130-220 l/min adjustable
Weight	2000 g

FEATURES :

- Fully CE Marked with low airflow indicator.
- Lightweight, robust, rubber coated, glass fibre re-enforced polyester construction.
- Triple protection screen system consisting of a polycarbonate inner, glass intermediate, and protective wire mesh.
- Detachable cape and muffler.

ORDER CODES

JH40210	Defender Helmet with air flow regulator, and cape and muffler.
JH40220	Mesh Outer - each
JH40230	Glass Intermediate - each
JH14010P	Inner Lens - each

Notes :

Requires air supply which meets or exceeds EN 12021

This product only provides correct performance when used in accordance with manufacturer's instructions.

www.sfeg.co.uk

Data Sheet DS-28-2